

RFID Token



Key Features

- Strong lamination housing
- Anti-collision and harsh resistant
- Low cost
- Additional ABS + Epoxy for waterproof

Application:

- Automatic production management
- Asset tracking
- Device embedded

Tag Spec.:

Material:	ABS, PC	IP Class	IP68
Thickness:	2.3/3/4.8/7.8mm for optional	Resistance:	Waterproof, Harsh resistant

Size:

With Hole	Token Size	Outer Hole Size	Inner Hole Size	Thickness	Chip
JYL-ADTH25	Dia.25mm	9mm	5mm	4.5mm	LF/HF
JYL-ADTH30A	Dia.30mm	8.6mm	5mm	4.5mm	LF/HF
JYL-ADTH30B	Dia.30mm	/	2.5mm	2.5mm	LF/HF
JYL-ADTH35	Dia.35mm	4mm	3.8mm	3.8mm	LF/HF/UHF
JYL-ADTH40	Dia.40mm	9mm	4.5mm	4.5mm	LF/HF/UHF
JYL-ADTH52	Dia.52mm	10.5mm	8.4mm	8.4mm	LF/HF/UHF
Without Hole	Token Size	Outer Hole Size	Inner Hole Size	Thickness	Chip
JYL-ADT12	Dia.12mm	/	/	3.5mm	HF
JYL-ADT20	Dia.20mm	/	/	2.5mm	LF/HF
JYL-ADT22	Dia.22mm	/	/	3.4mm	LF/HF
JYL-ADT25	Dia.25mm	/	/	2.5mm	LF/HF
JYL-ADT27	Dia.27mm	/	/	3mm	LF/HF
JYL-ADT30	Dia.30mm	/	/	2.8mm	LF/HF

Optional Craft:

Coding:	Chip Encoding
Custom logo:	Silkscreen printing, Laser engrave
ID Number Printing:	Laser engrave
On Metal:	Anti-Metal Ferrite Layer optional
Adhesive:	Ordinary Adhesive sticker, 3M Adhesive Layer Optional
Warranty:	1 year


Self-adhesive Tag



White Tag



Tag with Epoxy



Logo Pre-printed Tag



The information contained on this Document is considered to be confidential material proprietary to JYL-Tech, and this information shall not be disclosed, duplicated or copied for any purpose, Nor made available for any third party without the prior consent to JYL-Tech.